



Hi-Speed USB 2.0 SVGA Converter

Supports Standard Monitors, 16 MB SDRAM Memory

**Easily connect another monitor, an LCD projector
or another SVGA device to notebook or desktop
computers**

The MANHATTAN® Hi-Speed USB 2.0 SVGA Converter helps increase productivity, improve “desktop” arrangements and extend the visual work area across dual monitors. It helps make word processing, editing and multi-tasking more effective with less-overlapped windows, fewer hidden palettes and better-organized views. Users can read email on one monitor and open attachments on the other. Large, complicated spreadsheets can be expanded and viewed without scrolling. Presentations are made more compelling with another monitor for more impact or viewing speaker notes on a separate display. The MANHATTAN Hi-Speed USB 2.0 SVGA Converter supports resolutions of up to 1280 x 1024 in 16-bit or 32-bit color, and its 16 MB SDRAM memory easily enhances the workspace without complicated installations or expensive equipment.

Easy to Install

The convenient Hi-Speed USB 2.0 connection eliminates the need to install another graphics card or struggle with compatibility issues. It's an ideal portable solution for notebook computers and desktop systems with graphics cards that lack additional outputs. With Plug and Play and hot-swap capabilities, it's easily installed without an external power supply on any Windows computer.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.

Model
179119





Model
179119

Features

- Easily adds a monitor to a computer to expand visual areas
- Ideal for notebook computers and graphics cards without additional outputs
- Primary, extended and mirror functions provide display continuity and dual views
- Supports resolutions up to 1280 x 1024 in 16-bit or 32-bit color
- Portable and connects to any USB port without conflicts or external power supplies
- Plug and Play; Windows compatible
- Lifetime Warranty

Specifications

STANDARDS AND CERTIFICATIONS

- Hi-Speed USB 2.0
- EHCI
- CE
- FCC

GENERAL

- Chipset: MCT Trigger
- Display memory: 16 MB SDRAM
- Bus-powered
- Connections: USB type A male; HD 15 female
- Supports Suspend and Wake modes

SUPPORTED RESOLUTIONS

- For Windows:
 - 5:4; 1280 x 1024; 16/32 bits
 - 4:3; 1024 x 768; 16/32 bits
 - 4:3; 800 x 600; 16/32 bits
 - 4:3; 640 x 480; 16/32 bits
- For Win CE:
 - 4:3; 800 x 600; 16/32 bits
 - 15:9; 800 x 480; 16/32 bits
 - 4:3; 640 x 480; 16/32 bits

PHYSICAL

- Case material: ABS plastic
- Dimensions: 8 x 4 x 2 cm (3.25 x 1.5 x 0.75 in.)
- Cable: 50 cm (19 in.)
- Weight: 2.8 oz. (79 g)

SYSTEM REQUIREMENTS

- Compatible with Windows 2000/XP/Vista and Win CE (with host device support)
- Win CE 5.0
- Available Hi-Speed USB 2.0 port

PACKAGE CONTENTS

- Hi-Speed USB 2.0 SVGA Converter
- Quick install guide and driver CD with user manual

For more information on MANHATTAN products, consult your local dealer or visit www.manhattan-products.com.


MANHATTAN[™]
BRINGING COMPUTERS TO LIFE

Copyright © MANHATTAN

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

MH-179119-DS-0708-02