



Gigabit Ethernet Rackmount

24-port, 802.1x security, Jumbo frame support and QoS High-Speed SATA NAS server for the home or office.

Boost your network speed.

The INTELLINET NETWORK SOLUTIONS Gigabit Ethernet Rackmount Web-Smart Switch offers an array of features while providing superior network throughput.

Extreme Flexibility

Twenty-four 10/100/1000 Mbps auto-sensing ports automatically detect optimal network speeds.

Easy Management

User-friendly Web-based management allows for easy administration.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all INTELLINET NETWORK SOLUTIONS products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.

Model
524063





Model
524063

Features

- 10/100/1000 auto-sensing ports — automatically detect optimal network speeds
- All RJ-45 ports with Auto-MDIX (auto uplink) support
- Supports NWay auto-negotiation
- Broadcast storm control with multicast packet rate settings
- Store and forward switching architecture
- Full/half duplex operation
- IEEE 802.3x flow control for full duplex
- Zero packet loss backpressure flow control for half duplex
- Packet filtering/forwarding rates: 1,488,000 pps (1000 Mbps), 148,800 pps (100 Mbps), 14,880 pps (10 Mbps)
- Supports port controls (speed, flow control and maximum frame size)
- Supports VLAN (tag-based and port-based)
- Supports link aggregation (trunking)
- Supports QoS (Quality of Service) with 2 priority levels
- Provides IEEE 802.1x port-based security
- Supports port mirroring
- Supports jumbo frames up to 9.6 kBytes
- 19" rackmount
- LEDs for power, link/activity, connection speed
- Lifetime Warranty

Specifications

Standards

- IEEE 802.1d (Spanning Tree Protocol)
- IEEE 802.1w (Rapid Spanning Tree Protocol)
- IEEE 802.1p (Traffic Prioritization)
- IEEE 802.1q (VLAN Tagging)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (Twisted Pair Gigabit Ethernet)
- IEEE 802.3ad (Link Aggregation)
- IEEE 802.3x (flow control, for full duplex mode)

General

- Media support:
 - 10Base-T Cat3, 4, 5 UTP/STP RJ-45
 - 100Base-TX Cat5 UTP/STP RJ-45
 - 1000Base-T Cat5e UTP/STP RJ-45
- Packet filter/forwarding rate:
 - 1,488,000 pps (1000 Mbps)
 - 148,800 pps (100 Mbps)
 - 14,880 pps (10 Mbps)
- Buffer memory: 500 kBytes
- MAC address table: 8192 entries
- Switch architecture: store and forward
- Certifications: FCC Class A, CE Mark

Configuration Options

- Port link speed: 10 Mbps, 100 Mbps, 1000 Mbps or auto-negotiation
- Flow control on/off per port
- Full/Half duplex per port
- VLAN, 24 groups
- Port Mirroring for all ports with sniffer port configuration
- Port Aggregation/Trunking: 8 groups

- with up to 24 member ports per trunk
- QoS, 2 priority levels
- Broadcast Storm configuration with ICMP rate, broadcast rate, multicast rate, flooded unicast rate
- Port Filter configuration: enable/disable, IP address, subnet mask, DHCP Server allowed/disallowed

LEDs

- Power
- Link/Act
- 1000 Mbps

Power

- Internal power supply, 100 – 240 V AC, 50/60 Hz
- Power consumption: 20 Watts (maximum)

Environmental

- Metal housing, 19" rackmount, 1 U
- Dimensions: 440 (L) x 220 (W) x 44 (H) mm (17.3 x 8.7 x 1.7 in.)
- Weight: 3.0 kg (6.4 lbs.)
- Operating temperature: 0 – 55°C (32 – 131°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -20 – 90°C (-4 – 194°F)

Package Contents

- Gigabit Ethernet Rackmount Web-Smart Switch
- External power adapter
- User manual

For more information on INTELLINET NETWORK SOLUTIONS products, consult your local dealer or visit www.intellinet-network.com.



Copyright © INTELLINET NETWORK SOLUTIONS