



2-Port Mini KVM Switch

2-Port USB, Audio Support

Operate two computers with one keyboard, mouse and monitor.

The INTELLINET NETWORK SOLUTIONS™ 2-Port KVM Switch is a mini KVM switch with integrated connection cables. Its USB support on the console side allows you to use a USB keyboard and mouse to access, control, boot and reboot two USB-enabled computers with only one keyboard and mouse and monitor.

Convenient PC Selection

Quickly and easily switch between workstations using the hotkey.

Audio Switching Offers an Uninterrupted Multimedia Experience

The audio switching function of this KVM Switch allows you to leverage the multimedia systems on each of your two computers. You can monitor the audio output of each computer without plugging on and off the audio cables.

Zero Cabling Hassles for KVM Users

This KVM Switch saves you cabling troubles with its two pair of 1.2 m (4 ft.) KVM connection cables. In fact, you have zero cabling troubles since you don't have to worry about finding suitable cables to fit — they come attached to the KVM switch.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all INTELLINET NETWORK SOLUTIONS products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.











Features

- Operate two USB computers with one keyboard, mouse and monitor
- Simply plug in the attached cables nothing else required!
- Full keyboard and mouse emulation for error-free booting
- Hot key commands and LED indicators for computer selection
- Audio output for speaker connection
- No software or power required
- Compatible with all operating systems
- Supports resolutions up to 1920 x 1440 pixels
- Lifetime Warranty

Specifications

GENERAL

- PC connections: 2
- Console connections: 1
- PC port connectors:
- 2 x USB type-A male (keyboard, mouse) 2 x HD15 M (video)
- 2 x 3.5 mm jack (sound card input) Integrated connection cables: 1.2 m (4 ft.)

- Console port connectors:
 Keyboard: USB type-A female
 Mouse: USB type-A female
 Monitor: HD15 female

- 1 x 3.5 mm jack (speaker output)
- Computer selection:
- Via hotkey
- Video resolution: max. 1920 x 1440
- Video bandwidth: max. 250 MHz

• FCC Class B, CE, RoHS

• 1 LED per channel

ENVIRONMENTAL

- Plastic housingScan interval: 3 seconds
- Scan Interval: 3 seconds
 Dimensions: 85 (W) x 75 (D) x 26 (H) mm (3.4 x 3 x 1 in.)
 Operating temperature: 0 50°C (32 122°F)
 Storage temperature: -20 60°C (-4 140°F)
 Weight: 360 g (12.7 oz.)

PACKAGE CONTENTS

- 2-Port Mini KVM Switch
- Quick installation guide

For more information on INTELLINET NETWORK SOLUTIONS products, consult your local dealer or visit **www.intellinet-network.com**.



Bringing Networks To Life

Copyright © INTELLINET NETWORK SOLUTIONS